

Code	Smart Hybrid System LT-SUN (ONLY HEATING)	Description	Image
Model: LT-SUN 7518			
1903071002	Split air-water heat pump SDDC-075-B Dimensions of inner body in mm (WxHxD): 880 x 360 x 800 Dimensions of outer body in mm (WxHxD): 732 x 410 x 319	Nominal heating capacity 8.6 kW, power supply 220-240 V. Heat pump's heating capacity regulation range: 1.50-10.50 kW.	
2104250200 left 2104250201 right	Pellet heating boiler Pelletherm 18 V.4 LT	Maximum heating capacity (at 80/60°C) 18 kW. Operation with wood pellets. Dimensions in mm (WxHxD) 780x1250x1080	
Model: LT-SUN 7525			
1903071002	Split air-water heat pump SDDC-075-B Dimensions of inner body in mm (WxHxD): 880 x 360 x 800 Dimensions of outer body in mm (WxHxD): 732 x 410 x 319	Nominal heating capacity 8.6 kW, power supply 220-240 V. Heat pump's heating capacity regulation range: 1.50-10.50 kW.	
2104250300 left 2104250301 right	Pellet heating boiler Pelletherm 25 V.4 LT	Maximum heating capacity (at 80/60°C) 25 kW. Operation with wood pellets. Dimensions in mm (WxHxD) 780x1250x1080	
Necessary components for hybrid system control			
3400003271	Climatic regulator RCE for high-temperature system (radiators/fan coils) or low-temperature system (radiant systems)	Power supply 110-230 Vac, 50 Hz, 48 Vdc. Contacts capacity: 5 A/230 Vac. Material: self-extinguishing PPO. Grey colour, Ral 7035	
3400003254	3-way electric, diverter valve Modulo Compact for DHW	Power supply 230V, connections 1" F-F	
Additional accessories (option)			
07245200	Remote control of heat pump CRONO TH	Integrated control of the heat pump and the heating system	
07245390 07245400	Steel water filter 1" F-F, Steel water filter 1 1/4" F-F	For mounting on the inlet of the heat pump	
07245220	Set of adjustable, anti-vibration supports (4 psc.)	For the installation of the heat pump	
02410500 02410502	Anti-vibration, flexible connection 1" MF, length 20 cm Anti-vibration, flexible connection 1 1/4" MF, length 20 cm	For the installation of the heat pump	
27180620 27180622	32x3 a pair of tightening, straight connections for multilayer pipes 1" M, with O-ring; 1" F, with O-ring	For refrigerant piping lines	
07245210	Temperature sensor for domestic hot water	It measures the temperature of warm, domestic water	
07514085	Flow temperature sensor	Measures the temperature of the supply water	
02769120	Boiler for domestic hot water with 200 l capacity	Provides domestic water with an option for connecting to a solar collector	
02769130	Boiler for domestic hot water with 300 l capacity	Provides domestic water with an option for connecting to a solar collector	